




















Elektromagnetické ventily

obj. č.	napětí cívky	vstup	výstup	počet vstupů/výstupů	
Elektromagnetické ventily univerzální „L”					
302004	230V	3/4"	10,5 mm	1/1	
302005	230V	3/4"	13,5 mm	1/1	
302012	24V	3/4"	10 mm	1/1	
302013	12V	3/4"	13,5 mm	1/1	
302008	230V	3/4"	10,5 mm	1/2	
302014	230V	3/4"	13,5 mm	1/2	
302015	230V	3/4"	10,5 mm	1/3	
302016	230V	3/4"	13,5 mm	1/3	
302010	220/240V	3/4"	14 mm	1/3	









Maximální provozní teplota kapaliny +90 °C

Elektromagnetické ventily

obj. č.	napětí cívky	vstup	výstup	počet vstupů/výstupů	
Elektromagnetické ventily univerzální „I”					
302007	230V	3/4"	10,5 mm	1/1	
302009	230V	3/4"	13,5 mm	1/1	
302017	24V	3/4"	10 mm	1/1	
302018	12V	3/4"	10,5 mm	1/1	
302006	230V	3/4"	10,5 mm	1/2	
302019	230V	3/4"	13,5 mm	1/2	
302020	230V	3/4"	10,5 mm	1/3	
302021	230V	3/4"	13,5 mm	1/3	
302011	230V	3/4"	3/4"	1/1	
302101	230V	3/4"	ø8	1/1	

Maximální provozní teplota kapaliny +90 °C

Elektromagnetické ventily









obj. č.	barva	průtok l/min	
Příslušenství k elektromagnetickým ventilům - škrtiče průtoku			
302902	zelená	0,25	
302905	žlutá	0,35	
302901	červená	0,5	
302903	čirá	1,2	
302906	bílá	2	
302904	oranžová	2,5	
302907	šedá	4,7	
302908	hnědá	5,5	

Maximální provozní teplota kapaliny +90 °C



obj. č.	název	
Vstupní filtr		
302950	Vstupní filtr	

Maximální provozní teplota kapaliny +90 °C

Elektromagnetické ventily

obj. č.	provedení	napětí cívky	vstup	výstup	počet vstupů /výstupů	
Elektromagnetické ventily Müller						
302201	„I“	230V	3/4"	12 mm	1/1	
302202	„I“	230V	3/4"	14 mm	1/1	
302203	„L“	230V	3/4"	14 mm	1/1	
302204	„I“	230V	1/2"	1/2"	1/1	
302205	„I“	230V	3/4"	3/4"	1/1	
302206	„L“	230V	3/4"	14 mm	1/2	
302207	„I“	230V	3/4"	14 mm	1/2	
302208	„I“	230V	3/4"	14 mm	1/3	

Maximální provozní teplota kapaliny +90 °C

obj. č.	napětí cívky	
Náhradní cívky k ventilům Müller		
302251	220V/240V, 50HZ/60HZ	
302252	24V AC	

Maximální provozní teplota kapaliny +90 °C